





Rotary screw compressors with V-belt drive – to 22 kW

Image	Model	Working pressure	FAD*) Overall package at working pressure	Max. operating pressure	Rated motor power	Dimensions W x D x H	Air connection	Sound pressure level **)	Weight
		bar	m³/min	bar	kW	mm		dB(A)	kg

SX – SK series

	SX 3	7.5 10	0.34 0.26	8 11	2.2	590 x 632 x 970	G ¾	59	140
	SX 4	7.5 10 13	0.45 0.36 0.26	8 11 15	3	590 x 632 x 970		60	140
	SX 6	7.5 10 13	0.60 0.48 0.37	8 11 15	4	590 x 632 x 970		61	145
	SX 8	7.5 10 13	0.80 0.67 0.54	8 11 15	5.5	590 x 632 x 970		64	155
	SM 9	7.5 10 13	0.90 0.75 0.56	8 11 15	5.5	630 x 762 x 1100	G ¾	64	200
	SM 12	7.5 10 13	1.20 1.01 0.77	8 11 15	7.5	630 x 762 x 1100		65	210
	SM 15	7.5 10 13	1.50 1.26 0.99	8 11 15	9	630 x 762 x 1100		66	220
	SK 22	7.5 10 13	2.00 1.68 1.32	8 11 15	11	750 x 895 x 1260	G 1	66	312
	SK 25	7.5 10 13	2.50 2.11 1.72	8 11 15	15	750 x 895 x 1260		67	320

ASK series

	ASK 27	7.5 10 13	2.60 2.18 1.70	8 11 15	15	1130 x 780 x 1255	G 1 ¼	65	390
	ASK 32	7.5 10 13	3.15 2.66 2.05	8 11 15	18.5	1130 x 780 x 1255		67	405
	ASK 35	7.5 10 13	3.50 2.96 2.37	8 11 15	22	1130 x 780 x 1255		69	420

Rotary screw compressors with 1:1 drive – to 500 kW



Image	Model	Working pressure	FAD*) Overall package at working pressure	Max. operating pressure	Rated motor power	Dimensions W x D x H	Air connection	Sound pressure level **)	Weight
		bar	m³/min	bar	kW	mm		dB(A)	kg

ASD–BSD series

	ASD 32	7.5 10 13	3.16 2.72 2.09	8 11 15	18.5	1350 x 921 x 1505	G 1 ¼	65	580
	ASD 37	7.5 10 13	3.90 3.12 2.65	8 11 15	22	1350 x 921 x 1505		66	655
	ASD 47	7.5 10 13	4.57 3.84 2.99	8 11 15	25	1350 x 921 x 1505		66	665
	ASD 57	7.5 10 13	5.51 4.44 3.67	8 11 15	30	1350 x 921 x 1505		69	720
	BSD 62	7.5 10 13	5.65 4.45 3.60	8 11 15	30	1530 x 1005 x 1700	G 1 ½	69	980
	BSD 72	7.5 10 13	7.00 5.59 4.40	8 11 15	37	1530 x 1005 x 1700		70	1015
	BSD 81	7.5 10 13	8.16 6.79 5.43	8 11 15	45	1530 x 1005 x 1700		72	1100

Image	Model	Working pressure	FAD*) Overall package at working pressure	Max. operating pressure	Rated motor power	Dimensions W x D x H	Air connection	Sound pressure level **)	Weight
		bar	m³/min	bar	kW	mm		dB(A)	kg

CSD–HSD series


	CSD 85	7.5 10 13	8.26 6.89 5.50	8.5 12 15	45	1760 x 1110 x 1900	G 2	70	1250
	CSD 105	7.5 10 13	10.14 8.18 6.74	8.5 12 15	55	1760 x 1110 x 1900		71	1290
	CSD 125	7.5 10 13	12.02 10.04 8.06	8.5 12 15	75	1760 x 1110 x 1900		72	1320
	CSDX 140	7.5 10 13	13.74 11.83 9.86	8.5 12 15	75	2110 x 1290 x 1950	G 2	71	1830
	CSDX 165	7.5 10 13	16.16 13.53 11.49	8.5 12 15	90	2110 x 1290 x 1950		72	1925
	DSD 142	7.5	13.62	9	75	2350 x 1730 x 2040	DN 65	68	2700
	DSD 172	7.5 10	16.12 13.20	8.5 12	90	2350 x 1730 x 2040		69	2850
	DSD 202	7.5 10 13	20.46 15.52 12.68	8.5 12 15	110	2350 x 1730 x 2040		70	3200
	DSD 238	7.5 10 13	23.80 19.92 14.80	8.5 12 15	132	2350 x 1730 x 2040		71	3400
	DSDX 243	7.5 10 13	24.10 20.12 14.90	8.5 12 15	132	2600 x 1980 x 2040	DN 80	70 78 ***)	3650
	DSDX 302	7.5 10 13	30.20 23.50 19.52	8.5 12 15	160	2600 x 1980 x 2040		71 78 ***)	4100
	ESD 352	7.5 10 13	36.20 29.72 23.10	8.5 12 15	200	2800 x 2000 x 2140	DN 125	75	4935
	ESD 442	7.5 10 13	42.20 35.40 28.92	8.5 12 15	250	2800 x 2000 x 2140		76	5000
	FSD 471	7.5 10 12	47.10 40.50 35.50	8 10 12	250	3000 x 2143 x 2360	DN 125	79	6625
	FSD 571	7.5 10 13	57.20 46.40 39.45	8 12 15	315	3000 x 2143 x 2360		79	6900
	HSD 651	7.5 10 13	66.1 53.4 43.0	8.5 12 15	360	3470 x 2145 x 2350	DN 150	71	8100
	HSD 711	7.5 10 13	71.8 59.4 46.2	8.5 12 15	400	3470 x 2145 x 2350		72	8500
	HSD 761	7.5 10 13	77.6 65.1 52.3	8.5 12 15	450	3470 x 2145 x 2350		72	8600
	HSD 831	7.5 10 13	83.4 70.8 58.4	8.5 12 15	500	3470 x 2145 x 2350		73	8700

*) Performance data in accordance with ISO 1217:2009, Annex C. **) Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, tolerance: ± 3 dB(A); ***) At high fan speed



Modular rotary screw compressors with refrigeration dryer & air receiver – to 15 kW

Image	Model	Working pressure	FAD*) overall package at working pressure	Max. operating pressure	Rated motor power	Dryer power consumption	Refrigerant	Pressure dew point	Air receiver capacity	Dimensions W x D x H	Air connection	Sound pressure level **)	Weight
		bar	m³/min	bar	kW	kW	Type	° C	l	mm		dB(A)	kg




SXC series

	SXC 3	7.5 10	0.34 0.26	8 11	2.2	0.25	R 134a	+ 6	215	620 x 980 x 1480	G ¾	68	285
	SXC 4	7.5 10 13	0.45 0.36 0.26	8 11 15	3.0	0.25	R 134a	+ 6	215	620 x 980 x 1480		69	285
	SXC 6	7.5 10 13	0.60 0.48 0.37	8 11 15	4.0	0.30	R 134a	+ 6	215	620 x 980 x 1480		69	290
	SXC 8	7.5 10 13	0.80 0.67 0.54	8 11 15	5.5	0.30	R 134a	+ 6	215	620 x 980 x 1480		69	300

AIRCENTER Series

	AIRCENTER 3	7.5 10	0.34 0.26	8 11	2.2	0.25	R 134a	+ 3	200	590 x 1090 x 1560	G ¾	59	285	
	AIRCENTER 4	7.5 10 13	0.45 0.36 0.26	8 11 15	3	0.25	R 134a	+ 3	200	590 x 1090 x 1560		60	285	
	AIRCENTER 6	7.5 10 13	0.60 0.48 0.37	8 11 15	4	0.27	R 134a	+ 3	200	590 x 1090 x 1560		61	290	
	AIRCENTER 8	7.5 10 13	0.80 0.67 0.54	8 11 15	5.5	0.27	R 134a	+ 3	200	590 x 1090 x 1560		64	300	
	AIRCENTER 9	7.5 10 13	0.90 0.75 0.56	8 11 15	5.5	0.35	R 134a	+ 3	270	630 x 1200 x 1716	G ¾	64	390	
	AIRCENTER 12	7.5 10 13	1.20 1.01 0.77	8 11 15	7.5	0.35	R 134a	+ 3	270	630 x 1200 x 1716		65	400	
	AIRCENTER 15	7.5 10 13	1.50 1.26 0.99	8 11 15	9	0.60	R 134a	+ 3	270	630 x 1200 x 1716		66	410	
	AIRCENTER 22	7.5 10 13	2.00 1.68 1.32	8 11 15	11	0.52	R 134a	+ 3	350	750 x 1370 x 1880		G 1	66	579
	AIRCENTER 25	7.5 10 13	2.50 2.11 1.72	8 11 15	15	0.52	R 134a	+ 3	350	750 x 1370 x 1880			67	587







SX T–SK T series, modular with refrigeration dryer – to 15 kW

	SX 3 T	7.5 10	0.34 0.26	8 11	2.2	0.25	R 134a	+ 3	-	590 x 900 x 970	G ¾	59	185
	SX 4 T	7.5 10 13	0.45 0.36 0.26	8 11 15	3	0.25	R 134a	+ 3	-	590 x 900 x 970		60	185
	SX 6 T	7.5 10 13	0.60 0.48 0.37	8 11 15	4	0.27	R 134a	+ 3	-	590 x 900 x 970		61	190
	SX 8 T	7.5 10 13	0.80 0.67 0.54	8 11 15	5.5	0.27	R 134a	+ 3	-	590 x 900 x 970		64	200
	SM 9 T	7.5 10 13	0.90 0.75 0.56	8 11 15	5.5	0.35	R 134a	+ 3	-	630 x 1074 x 1100	G ¾	64	275
	SM 12 T	7.5 10 13	1.20 1.01 0.77	8 11 15	7.5	0.35	R 134a	+ 3	-	630 x 1074 x 1100		65	285
	SM 15 T	7.5 10 13	1.50 1.26 0.99	8 11 15	9	0.60	R 134a	+ 3	-	630 x 1074 x 1100		66	295
	SK 22 T	7.5 10 13	2.00 1.68 1.32	8 11 15	11	0.52	R 134a	+ 3	-	750 x 1240 x 1260	G 1	66	387
	SK 25 T	7.5 10 13	2.50 2.11 1.72	8 11 15	15	0.52	R 134a	+ 3	-	750 x 1240 x 1260		67	395

Modular rotary screw compressors with refrigeration dryer – to 132kW

Image	Model	Working pressure	FAD*) overall package at working pressure	Max. operating pressure	Rated motor power	Dryer power consumption	Refrigerant	Pressure dew point	Air receiver capacity	Dimensions W x D x H	Air connection	Sound pressure level **)	Weight
		bar	m³/min	bar	kW	kW	Type	° C	l	mm		dB(A)	kg

ASK T–DSD T series



	ASK 27 T	7.5 10 13	2.60 2.18 1.70	8 11 15	15	0.68	R 134a	+ 3	-	1480 x 780 x 1255	G 1 ¼	65	465
	ASK 32 T	7.5 10 13	3.15 2.66 2.05	8 11 15	18.5	0.68	R 134a	+ 3	-	1480 x 780 x 1255		67	480
	ASK 35 T	7.5 10 13	3.50 2.96 2.37	8 11 15	22	0.68	R 134a	+ 3	-	1480 x 780 x 1255		69	495
	ASD 32 T	7.5 10 13	3.16 2.72 2.09	8 11 15	18.5	0.53	R 134a	+ 3	-	1850 x 921 x 1505	G 1 ¼	65	740
	ASD 37 T	7.5 10 13	3.90 3.12 2.65	8 11 15	22	0.53	R 134a	+ 3	-	1850 x 921 x 1505		66	820
	ASD 47 T	7.5 10 13	4.57 3.84 2.99	8 11 15	25	0.8	R 134a	+ 3	-	1850 x 921 x 1505		66	830
	ASD 57 T	7.5 10 13	5.51 4.44 3.67	8 11 15	30	0.8	R 134a	+ 3	-	1850 x 921 x 1505		69	890
	BSD 62 T	7.5 10 13	5.65 4.45 3.60	8 11 15	30	0.8	R 134a	+ 3	-	2080 x 1005 x 1700	G 1 ½	69	1200
	BSD 72 T	7.5 10 13	7.00 5.59 4.40	8 11 15	37	0.8	R 134a	+ 3	-	2080 x 1005 x 1700		70	1250
	BSD 81 T	7.5 10 13	8.16 6.79 5.43	8 11 15	45	1.1	R 134a	+ 3	-	2080 x 1005 x 1700		G 2	72
	CSD 85 T	7.5 10 13	8.26 6.89 5.50	8.5 12 15	45	0.8	R 134a	+ 3	-	2160 x 1110 x 1900	G 2	70	1410
	CSD 105 T	7.5 10 13	10.14 8.18 6.74	8.5 12 15	55	0.8	R 134a	+ 3	-	2160 x 1110 x 1900		71	1450
	CSD 125 T	7.5 10 13	12.02 10.04 8.06	8.5 12 15	75	1.1	R 134a	+ 3	-	2160 x 1110 x 1900		72	1510
	CSDX 140 T	7.5 10 13	13.74 11.83 9.86	8.5 12 15	75	1.2	R 134a	+ 3	-	2510 x 1290 x 1950	G 2	71	2045
	CSDX 165 T	7.5 10 13	16.16 13.53 11.49	8.5 12 15	90	1.2	R 134a	+ 3	-	2510 x 1290 x 1950		72	2140
	DSD 142 T	7.5	13.62	9	75	2.1	R 134a	+ 3	-	3310 x 1730 x 2040	DN 65	68	3100
	DSD 172 T	7.5 10	16.12 13.20	8.5 12	90	2.1	R 134a	+ 3	-	3310 x 1730 x 2040		69	3250
	DSD 202 T	7.5 10 13	20.46 15.52 12.68	8.5 12 15	110	2.35	R 134a	+ 3	-	3310 x 1730 x 2040		70	3650
	DSD 238 T	7.5 10	23.80 19.92	8.5 12	132	2.35	R 134a	+ 3	-	3310 x 1730 x 2040		71 79***)	3850
		13	14.80	15									

* Performance data in accordance with ISO 1217:2009, Annex C. ** Sound pressure level as per ISO 2151 and basic standard ISO 9614-2, tolerance: ± 3 dB(A); *** At high fan speed












Modular rotary screw compressors with SIGMA FREQUENCY CONTROL – to 515 kW

Image	Model	Working pressure	FAD*) overall package at working pressure	Max. operating pressure	Rated motor power	min. pressure bandwidth	Speed range min.–max.	Frequency range min.–max.	Dimensions W x D x H	Air connection	Sound pressure level **)	Weight
		bar	m³/min	bar	kW	bar	rpm	Hz	mm		dB(A)	kg

SM SFC–CSDX SFC series

	SM 12 SFC	7.5	0.34 - 1.24	8	7.5	± 0.1	1200 - 3780	20 - 63	630 x 762 x 1100	G 3/4	67	220
		10	0.34 - 1.04	11			1500 - 3780	25 - 63				
		13	0.30 - 0.78	15			1800 - 3780	30 - 63				
	SK 22 SFC	7.5	0.62 - 1.98	8	11	± 0.1	1200 - 3510	20 - 58.5	750 x 895 x 1260	G 1	67	329
		10	0.63 - 1.67	11			1500 - 3552	25 - 59.2				
		13	0.57 - 1.37	15			1800 - 3660	30 - 61.0				
	SK 25 SFC	7.5	0.81 - 2.55	8	15	± 0.1	1200 - 3660	20 - 61.0	750 x 895 x 1260	G 1	68	337
		10	0.84 - 2.25	11			1500 - 3696	25 - 61.6				
		13	0.83 - 1.90	15			1800 - 3872	30 - 64.5				
	ASK 32 SFC	7.5	0.77 - 2.90	8	18.5	± 0.1	1200 - 3900	20 - 65	1130 x 850 x 1255	G 1 1/4	68	425
		10	0.59 - 2.38	11			1200 - 3960	20 - 66				
		13	0.67 - 1.84	15			1800 - 3780	30 - 63				
	ASD 32 SFC	7.5	0.69 - 3.32	8	18.5	± 0.1	900 - 3690	15 - 61.5	1850 x 921 x 1505	G 1 1/4	67	715
		10	0.90 - 2.86	10			1200 - 3240	20 - 54				
		13										
	ASD 37 SFC	7.5	0.82 - 4.05	8.5	22	± 0.1	900 - 3840	15 - 64	1850 x 921 x 1505	G 1 1/4	68	790
		10	0.61 - 3.58	15			900 - 4050	15 - 67.5				
		13	0.56 - 3.17	15			900 - 3600	15 - 60				
	ASD 47 SFC	7.5	1.07 - 4.92	8.5	25	± 0.1	900 - 3780	15 - 63	1850 x 921 x 1505	G 1 1/4	68	800
		10	0.79 - 4.12	11			900 - 3960	15 - 66				
		13	0.60 - 3.60	15			900 - 4200	15 - 70				
	BSD 72 SFC	7.5	1.57 - 6.25	8.5	37	± 0.1	900 - 3330	15 - 55.5	2080 x 1005 x 1700	G 1 1/2	72	1220
		10	1.16 - 5.34	11			900 - 3600	15 - 60				
		13	0.87 - 4.45	15			900 - 3720	15 - 62				
	CSD 85 SFC	7.5	1.95 - 8.08	8.5	45	± 0.1	900 - 3492	15 - 58.2	1760 x 1110 x 1900	G 2	71	1260
		10	1.48 - 6.91	12			900 - 3730	15 - 62.2				
		13	1.07 - 5.92	15			900 - 4020	15 - 67				
	CSD 105 SFC	7.5	2.19 - 9.85	8.5	55	± 0.1	900 - 3606	15 - 60.1	1760 x 1110 x 1900	G 2	72	1380
		10	1.90 - 8.35	12			900 - 3690	15 - 61.5				
		13	1.36 - 6.88	15			900 - 3840	15 - 64				
	CSD 125 SFC	7.5	2.84 - 12.00	8.5	75	± 0.1	900 - 3624	15 - 60.4	1760 x 1110 x 1900	G 2	73	1400
		10	2.05 - 10.53	12			900 - 3900	15 - 65				
		13	1.79 - 8.75	15			900 - 4020	15 - 67				
	CSDX 140 SFC	7.5	3.39 - 13.17	8.5	75	± 0.1	900 - 3330	15 - 55.5	2110 x 1290 x 1950	G 2	72	1835
		10	2.81 - 11.33	12			900 - 3410	15 - 56.8				
		13	1.90 - 9.73	15			900 - 3660	15 - 61				
	CSDX 165 SFC	7.5	3.84 - 15.84	8.5	90	± 0.1	900 - 3486	15 - 58.1	2110 x 1290 x 1950	G 2	73	2025
		10	3.29 - 13.84	12			900 - 3590	15 - 59.8				
		13	2.70 - 11.70	15			900 - 3660	15 - 61				




DSC SFC–HSD SFC series

	DSD 142 SFC	7.5	3.60 - 14.80	9	75	± 0.1	450 - 1635	15 - 54.5	2905 x 1730 x 2040	DN 65	69	3100
		10	3.60 - 16.33	10			450 - 1815	15 - 60.5				
		13	3.55 - 14.20	15			450 - 1590	15 - 53				
		13	3.55 - 14.20	15			450 - 1590	15 - 53				
	DSD 172 SFC	7.5	4.25 - 20.30	10	110	± 0.1	450 - 1905	15 - 63.5	2905 x 1730 x 2040	DN 65	71	3730
		10	4.00 - 17.30	10			450 - 1680	15 - 56				
		13	3.25 - 14.95	15			450 - 1770	15 - 59				
		13	3.25 - 14.95	15			450 - 1770	15 - 59				
	DSD 202 SFC	7.5	5.93 - 22.50	10	132	± 0.1	450 - 1650	15 - 55	2905 x 1730 x 2040	DN 65	72	3870
		10	5.80 - 20.00	10			450 - 1500	15 - 50				
		13	3.56 - 16.00	15			450 - 1620	15 - 54				
		13	3.56 - 16.00	15			450 - 1620	15 - 54				
	DSD 238 SFC	7.5	6.62 - 26.90	8.5	132	± 0.1	450 - 1680	15 - 56	3155 x 1945 x 2040	DN 80	71	4150
		10	5.60 - 23.73	12			450 - 1770	15 - 59				
		13	3.56 - 19.00	15			450 - 1920	15 - 64				
		13	3.56 - 19.00	15			450 - 1920	15 - 64				
	DSDX 243 SFC	7.5	6.62 - 30.60	8.5	160	± 0.1	450 - 1920	15 - 64	3155 x 1945 x 2040	DN 80	72	4600
		10	5.60 - 26.70	12			450 - 2010	15 - 67				
		13	3.56 - 21.10	15			450 - 2160	15 - 72				
		13	3.56 - 21.10	15			450 - 2160	15 - 72				
	ESD 352 SFC	7.5	8.58 - 33.38	8.5	200	± 0.1	450 - 1668	15 - 55.6	3100 x 2000 x 2140	DN 125	76	4848
		10	6.43 - 27.43	12			450 - 1730	15 - 57.7				
		13	5.17 - 23.70	15			450 - 1800	15 - 60				
		13	5.17 - 23.70	15			450 - 1800	15 - 60				
	ESD 442 SFC	7.5	10.14 - 41.52	8.5	250	± 0.1	450 - 1746	15 - 58.2	3100 x 2000 x 2140	DN 125	77	4876
		10	8.33 - 36.00	12			450 - 1870	15 - 62.3				
		13	6.13 - 29.50	15			450 - 1920	15 - 64.0				
		13	6.13 - 29.50	15			450 - 1920	15 - 64.0				
	FSD 571 SFC	7.5	13.30 - 52.15	8.5	315	± 0.1	450 - 1665	15 - 55.5	3610 x 2143 x 2360	DN 125	80	7610
		10	9.80 - 45.10	15			450 - 1920	15 - 64				
		13	9.40 - 39.70	15			450 - 1710	15 - 57				
	HSD 651 SFC	7.5	10.1 - 66.0	8.5	382	± 0.1	450 - 1770	15 - 59	4370 x 2145 x 2350	DN 150	73	9100
		10	8.4 - 56.1	12			450 - 1830	15 - 61				
		13	8.0 - 54.0	15			450 - 1770	15 - 59				
		13	8.0 - 54.0	15			450 - 1770	15 - 59				
	HSD 761 SFC	7.5	11.7 - 75.9	8.5	410	± 0.1	450 - 1650	15 - 55	4370 x 2145 x 2350	DN 150	74	9600
		10	9.8 - 63.8	12			450 - 1710	15 - 57				
		13	8.0 - 54.0	15			450 - 1770	15 - 59				
	HSD 831 SFC	7.5	11.8 - 86.0	8	515	± 0.1	450 - 1830	15 - 61	4370 x 2145 x 2350	DN 150	75	10100
		10	9.8 - 73.6	12			450 - 1890	15 - 63				
		13	9.4 - 62.6	15			450 - 1710	15 - 57				





Modular rotary screw compressors with SIGMA FREQUENCY CONTROL and refrigeration dryer – to 132 kW

Image	Model	Working pressure	FAD*) overall package at working pressure	Max. operating pressure	Rated motor power	Speed range min.–max.	Frequency range min.–max.	Dryer power consumption	Refrigerant	Pressure dew point	Dimensions W x D x H	Air connection	Sound pressure level **)	Weight
		bar	m³/min	bar	kW	rpm	Hz	kW	Type	° C	mm		dB(A)	kg

AIRCENTER SFC series

	AIRCENTER 12 SFC	7.5	0.34 - 1.24	8	7.5	1200 - 3780	20 - 63	0.35	R 134a	+ 3	630 x 1200 x 1716	G 3/4	67	410		
		10	0.34 - 1.04	11											1500 - 3780	25 - 63
		13	0.30 - 0.78	15											1800 - 3780	30 - 63
	AIRCENTER 22 SFC	7.5	0.62 - 1.98	8	11	1200 - 3510	20 - 58.5	0.52	R 134a	+ 3	750 x 1370 x 1880	G 1	67	596		
		10	0.63 - 1.67	11											1500 - 3552	25 - 59.2
		13	0.57 - 1.37	15											1800 - 3660	30 - 61.0
	AIRCENTER 25 SFC	7.5	0.81 - 2.55	8	15	1200 - 3660	20 - 61.0	0.52	R 134a	+ 3	750 x 1370 x 1880	G 1	68	604		
		10	0.84 - 2.25	11											1500 - 3696	25 - 61.6
		13	0.83 - 1.90	15											1800 - 3872	30 - 64.5

SM T SFC–DSD T SFC series

	SM 12 T SFC	7.5	0.34 - 1.24	8	7.5	1200 - 3780	20 - 63	0.35	R 134a	+ 3	630 x 1074 x 1100	G 3/4	67	295		
		10	0.34 - 1.04	11											1500 - 3780	25 - 63
		13	0.30 - 0.78	15											1800 - 3780	30 - 63
	SK 22 T SFC	7.5	0.62 - 1.98	8	11	1200 - 3510	20 - 58.5	0.52	R 134a	+ 3	750 x 1240 x 1260	G 1	67	404		
		10	0.63 - 1.67	11											1500 - 3652	25 - 58.2
		13	0.57 - 1.37	15											1800 - 3660	30 - 61.0
	SK 25 T SFC	7.5	0.81 - 2.55	8	15	1200 - 3660	20 - 61.0	0.52	R 134a	+ 3	750 x 1240 x 1260	G 1	68	412		
		10	0.84 - 2.25	11											1500 - 3696	25 - 61.6
		13	0.83 - 1.90	15											1800 - 3872	30 - 64.5
	ASK 32 T SFC	7.5	0.77 - 2.90	8	18.5	1200 - 3900	20 - 65	0.68	R 134a	+ 3	1480 x 850 x 1255	G 1 1/4	68	50		